

SM1P SERIES

The Versatile Solution for Safe Communication in Noisy Workplaces

The SM1P provides essential features and benefits to improve safety, reliability, and efficiency. Sensear's new industrial headset platform offers a robust design adhering to higher noise reduction standards. These headsets use Sensear's SENS® Technology to enhance speech and suppress noise while the noise-canceling boom mic filters out background noises so that clear speech is transmitted through the microphone. SM1P's upgraded Bluetooth® module also allows for the streaming of audio to the headset. The new cable connection at ear cup allows you to use it as a wired headset along with Bluetooth® and Short-Range or unplug the cable and use it as a completely wireless headset via Bluetooth® and Short-Range.

Intrinsically Safe versions are available for use in Hazardous Environments.



360°
Situational
Awareness



Electronic
Volume
Limiter



Cellular
Bluetooth®



Protects
Hearing



Short-Range



Two-Way
Radios



Intrinsic
Safety



Speech Enhancement
Noise Suppression



Face-to-Face
Communication



SM1P-IS model

FEATURES AND BENEFITS

- Clear two-way radio communication in high-noise environments
- Bluetooth® cellular connection for conversation and audio streaming
- Limit 'in-ear' exposure to 82 dB(A)
- Compatible with leading two-way radios via removable wired connection or Bluetooth®
- Improved Short-Range (SR) with VOX capabilities and additional channel banks
- FM Radio enable/disable: Allows users to listen to commercial FM Radio stations
- Upgraded battery life (up to 24 hours) for use in multiple shifts
- Available in Headband, Behind-the-Neck, and Helmet Mount style
- Up to 27dB NRR / 33dB SNR / 31dB, Class 5 SLC80
- SENS® Technology - remain aware of surrounding noises and hazards
- Enhances speech while suppressing background noise to a safe level
- Noise-canceling boom microphone
- Intrinsically safe SM1P-IS series certified to: TIA-4950-A, CSA C22.2 No. 157.92, & UL 913 5th Edition with a hazardous location rating of Class I, II, III, Division 1 & 2, Groups A - G, T4 -20°C to +40°C, T3C -20°C to +50°C



Experience SENS®
Technology!



Styles



Type	Non-IS Part #	IS Part #
Headband	SM1PB002	SM1PBI502



Type	Non-IS Part #	IS Part #s
Behind-the-Neck	SM1PE002	SM1PEI502



Type	Non-IS Part #	IS Part #s
Helmet Mount	SM1PH002	SM1PHI502

Technical Specifications

General

Headset Type	Headband (HB)	Behind-the-Neck (BTN)	Helmet Mount (HM)
Sensear Part Number	SM1PB002 / SM1PBI502	SM1PE002 / SM1PEI502	SM1PH002 / SM1PHI502
Weight	495 g (17.46 oz.)	428 g (15.09 oz.)	480g (16.93 oz.)
IP Rating	IP54		
Operating temperature	-20°C to +60°C (-4°F to 140°F)		

Hearing Protection

Volume limiter	82 dB(A) [programmable] – only applicable when headset is powered on		
Region	Australia / NZ	USA / Canada	Europe
Standard	AS/NZS 1270	ANSI S3.19	EN352-1/EN352-3
Result	SLC80	NRR	SNR
HB	31dB, Class 5	27dB	33dB
BTN	27dB, Class 5	24dB	30dB
HM	26dB, Class 5	23dB	31dB

Power

	Non-Intrinsically Safe	Intrinsically Safe
Battery type	Rechargeable - lithium polymer	Rechargeable - lithium ion
Battery capacity	2650 mAh	2250 mAh
Operating time	24 hours	24 hours (wired) / 18 hours (Bluetooth®/SR)
Charge time	5 hours	4 hours
Charging temperature	0°C to +40°C (32°F to 104°F)	0°C to +40°C (32°F to 104°F)

Communication

Face-to-Face SENS® Mode	SENS® voice pickup limit of 95 dB(A)		
Voice Transmission	Noise-canceling boom microphone VOX capable when used in Short-Range mode for headset-to-headset communication VOX capable when connected to VOX enabled two-way radio* *Must be verified and tested for compatibility with the two-way radio		
Wired Connectivity	6-pin Hirose connector	Two-way radio audio through headset without headset battery**	Audio revert to radio when headset Hirose connector disconnected**
Short-Range	Half-duplex communications	Up to 8 programmable FM channels	Up to 50 meters (164 feet)
Bluetooth®	Bluetooth® 3.0: HFP (8KHz and 16KHz), HSP, A2DP		15 meters (49 feet)

**Dependent on radio type and compatible SRCK radio cable

Short-Range

Region	EIRP (uW)	Standards	FM Freq. range (MHz)
1	8.02	AS/NZS 4268	88.1 – 107.9
2	0.048	EN301357-1	88.1 – 107.9
3	0.012	FCC-15.239 & IC	88.1 – 97.0

FM Radio enable/disable option: Allows user to listen to commercial FM radio stations

Intrinsic Safety for Hazardous Locations

SM1P-IS series:

TIA-4950-A, CSA C22.2 No. 157.92, & UL 913 5th Edition with a hazardous location rating of Class I, II, III, Division 1 & 2, Groups A - G, T4 -20°C to +40°C, T3C -20°C to +50°C

Noise is Everywhere



OIL & GAS / PETROCHEMICAL / ENERGY



CONSTRUCTION / HEAVY EQUIPMENT



MANUFACTURING / MINING (ABOVE GROUND)



Your Local Dealer
Magnum Electronics, Inc.
927 Horsepond Rd,
Dover, DE 19901
302-734-9250

Sensear Pty Ltd
4 Hehir Street
Belmont, WA, 6104
Australia
Toll-Free: 1-300-859-120

Sensear Inc.
150 South Washington St
Suite C
Carpentersville, IL 60110
United States
Toll-Free: 1-888-973-6732

SENS
TECHNOLOGY by Sensear

www.sensear.com